



Material Safety Data Sheet

MSDS: 302

SECTION 1: CHEMICAL PRODUCT AND COMPANY INFORMATION

| | | |
|--|---|--|
| Company: IDQ Operating, Inc. 2901 W Kingsley Rd. Garland, Texas 75041 Phone No.: 1-888-396-0422 CHEMTREC Phone No.: 1-800-424-9300 | HAZARD RATING Health: 1 Fire: 0 Reactivity: 0 Special: -- Toxicity: 1 | SCALE 0 = Insignificant 1 = Slight 2 = Moderate 3 = High 4 = Extreme |
|--|---|--|

Product Description: R134a Automotive Refrigerant (packaged in non-reusable 30 lb cylinders)

Product Code: 302

MSDS Date: 3-04-2010

SECTION 2: COMPOSITION AND INFORMATION ON INGREDIENTS

| No. | Description | CAS Reg. No. | Units | Amount |
|-----|---------------------------|--------------|-------|--------|
| 1 | 1,1,1,2-Tetrafluoroethane | 811-97-2 | % vol | 100 |

SECTION 3: HAZARDS INFORMATION

Portals of Entry: Inhalation, eye contact, and skin contact.

Inhalation: Inhalation of high vapor concentrations can cause anesthetic effects including dizziness, weakness, nausea, and unconsciousness. It can act as an asphyxiant by limiting available oxygen. Very high doses can cause abnormal heart rhythm which is potentially fatal. Breathing high concentration vapors or prolonged breathing vapors can cause irritation of the nose, throat, and lungs as well as headaches, drowsiness, central nervous system (CNS) depression, and fatigue. Extreme inhalation can cause loss of coordination and unconsciousness.

Eye Contact: Liquid splashes or vapor spray may cause freeze burns. Vapors can cause eye irritation.

Skin Contact: Vapor spray can cause freeze burns. Product can cause eye irritations.

Ingestion: The product is a gas at Standard Temperature and Pressure (STP) which would allow the product to be ingested.

Delayed Effects: Prolonged and repeated overexposure can cause irritation of the respiratory tract and mucous membranes, and kidney effects.

HEALTH EFFECTS FROM OVEREXPOSURE:

Primary Routes of Exposure: Skin and inhalation.

SECTION 4: FIRST AID MEASURES

Inhalation: Inhalation under normal exposure should not cause problems; however if inhalation has resulted in symptoms, move patient to fresh air. If breathing is difficult, give oxygen. Give artificial respiration if breathing has stopped. Get prompt medical attention.

Eye Contact: Immediately flush eyes with a large amount of water for at least 15 minutes. If symptoms exist and/or persist, get prompt medical attention.

Skin Contact: Wash affected skin areas thoroughly with soap and water. Remove contaminated clothing. If skin irritation persists, see a physician.

Ingestion: If swallowed, give large quantities of water to drink. Induce vomiting. Careful gastric lavage may be indicated. Immediately see a physician. Never give anything by mouth nor induce vomiting of an unconscious person.

SECTION 5: FIRE FIGHTING MEASURES

Unusual Hazards: Toxic fumes are generated when material is exposed to fire and fire conditions.

Extinguishing Agents: Use the following extinguishing media when fighting fires involving this material: polar solvent foam, carbon dioxide, dry chemical, and water spray.

Personal Protective Equipment: Wear self-contained breathing apparatus and full protective gear.

Special Precautions: Use water spray to cool large containers exposed to fire. Vapors are denser than air and will have a tendency to accumulate in lower areas which can cause the vapors to concentrate and suffocate.

FIRE AND EXPLOSIVE PROPERTIES:

Flash Point (°C): Non-Flammable at STP

Auto-Ignition Temperature (°C): >350

Lower Explosive Limit (°C): Non-Flammable at STP

Upper Explosive Limit (°C): Non-Flammable at STP

SECTION 6: ACCIDENTAL SPILL OR LEAK RELEASE INFORMATION

Personal Protection: Appropriate protective equipment must be worn when handling a large spill of this material. See the PERSONAL PROTECTION MEASURES Section for recommendations. If exposed to material during clean-up operations, see the FIRST AID PROCEDURES Section for actions to follow.

Procedures: Evacuate the spill area. Ventilate the spill area. Avoid breathing vapor.

SECTION 7: HANDLING AND STORAGE

Storage Conditions: Store in a cool, well ventilated place. Keep containers dry. Store product away from reactive and corrosive materials. The minimum recommended storage temperature for this material is -29° C/ -20° F. The maximum storage temperature is 49° C/ 120° F.

Handling Procedures: Avoid causing and inhaling high concentrations of vapor. The vapor concentration levels in air need to be kept below occupational exposure limits and keep as low as practicable. Do not mix product with air or oxygen under pressure. Avoid exposure of product to flame or very hot surfaces. Vapors can be evolved when material is being used in processing operations. See FACILITY CONTROL MEASURES Section for types of ventilation required.

SECTION 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Respiratory Protection: A respiratory protection program meeting OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use. If respiratory protection is needed, use, MSHA-NIOSH approved respirator for organic vapors. None required if airborne concentrations are maintained below the TWA/TLV's listed in the COMPONENT EXPOSURE INFORMATION Section.

Up to 10 times the TWA/TLV: Wear a half-mask, air purifying respirator.

Up to 1000 ppm organic vapor: Wear an approved full-face piece, air-purifying respirator.

Above 1000 ppm organic vapor or unknown: Wear an approved positive pressure mode, or an approved full-face piece airline respirator in the positive pressure mode with emergency escape provisions.

Air purifying respirators should be equipped with organic vapor cartridges.

Eye Protection: Use eye goggles and/or face shield.

Hand Protection: The gloves listed below may provide protection against permeation. Gloves of other chemically resistant materials may not provide adequate protection: Polyvinyl alcohol and Viton.

Gloves should be removed and replaced immediately if there is any indication of degradation or chemical breakthrough.

Other Protection: Use chemically resistant apron or other impervious clothing to avoid prolonged or repeated skin contact.

FACILITY CONTROL MEASURES:

Ventilation: Use normal local exhaust ventilation with a minimum capture velocity of 100 ft/min (0.5 m/sec) at the point of vapor evolution.

Other Protective Equipment: Facilities storing and utilizing this material should be equipped with an eyewash facility and a safety shower.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

TYPICAL PHYSICAL PROPERTIES:

| PROPERTY | METRIC UNITS | ENGLISH UNITS |
|---|---------------------------|---------------------------|
| Appearance: | Product in 30 lb Cylinder | Product in 30 lb Cylinder |
| Color: | Colorless | Colorless |
| State: | Liquid under Gas Pressure | Liquid under Gas Pressure |
| Odor Characteristics: | Ethereal | Ethereal |
| Viscosity, as Liquid (CP 20° C); [CP 68° F]: | 18 | 18 |
| Specific Gravity (d/do 4°C); [d/do 39°F] | 1.27 | 1.27 |
| Vapor Density (Air = 1.0): | 3.3 | 3.3 |
| Vapor Pressure (mm Hg @ 20° C); [psia]: | 4268 | 85.6 |
| Melting Point (°C); [°F]: | Extremely Low; < -26 °C | Extremely Low; < -15 °F |
| Boiling Point (°C); [°F]: | -26.2 | -15.1 |
| Solubility in Water (gr/100 cm ³); [lb/100 in ³]: | 0; Non-soluble | 0; Non-soluble |
| Soluble In: | Ether | Ether |
| Solubility Parameters δ_p , δ_{hb} (gr-cal/mol) | 2.1, 1.7 | 2.1, 1.7 |
| Evaporation Rate (n-butyl acetate = 1.0): | > 120 | > 120 |
| pH (product or water extract) | < 7 | < 7 |
| Percent Volatility (% wt): | 100 | 100 |
| Molecular Weight (gr/mol); [lb/mol] | 102 | 0.225 |

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Hazardous Decomposition Products: Thermal decomposition may yield toxic decomposition products which include alkyl low molecular weight components, organic chlorides, COx, hydrochloric acid, hydrofluoric acid, and organic pyrolytic components.

Hazardous Polymerization: Product will not undergo polymerization.

Incompatibility: Avoid contact with strong oxidizing and reducing agents, fine particulate metals, magnesium and alloy containing more than 2 percent magnesium. Product can react under certain conditions with alkali or alkali earth metals such as sodium, potassium or barium and other Group IA and IIA of the Periodic Table of Elements.

SECTION 11: TOXICOLOGICAL INFORMATION

COMPONENT EXPOSURE INFORMATION:

Component Information:

| No. | Description | CAS Reg. No. | Units | Amount | Max. Amount % Wt. |
|-----|---------------------------|--------------|-------|--------|----------------------|
| 1 | 1,1,1,2-Tetrafluoroethane | 811-97-2 | % vol | 100 | 100 |

Exposure Information for Specific Component:

| No. | Health Flammable | | Component Units | OSHA | | ACGIH | | | |
|-----|------------------|--------|--------------------|------|------|-------|------|------|-----|
| | Rating | Rating | | TWA | STEL | TWA | STEL | IDLH | HAP |
| 1 | 1 | 0 | ppm | 1000 | NA | NA | NA | NA | No |

NA: Not Available; ppm: parts per million

Note: 1 ppm equals 3.8 mg/m³; 5 ppm equals 19 mg/m³; 10 ppm equals 38 mg/m³; 100 ppm equals 380 mg/m³.

SECTION 12: ECOLOGICAL INFORMATION

Persistence and Degradation: Decomposes comparatively rapidly in the lower atmosphere (troposphere). Atmospheric lifetime is 15.6 years. Products of decomposition will be highly dispersed and hence will have a very low concentration. It is not a significant contributor to photochemical smog and is not considered to be a VOC. It is not considered as an ozone depleting chemical.

SECTION 13: DISPOSAL INFORMATION

WASTE DISPOSAL:

Procedure: For disposal, dispose this material at a facility that complies with local, state, and federal regulations.

SECTION 14: TRANSPORTATION INFORMATION

DOT Hazard Description:

Proper Shipping Name: 1,1,1,2-TETRAFLUOROETHANE
Hazard Class: 2.2
Identification Number: UN 3159
Packing Group: NA
Hazardous Substance (RQ): NA
Placard/Label: 2

SECTION 15: REGULATORY INFORMATION

EPA Regulation:

SARA SECTION 355/370, and 372: This product does not contain any chemicals subject to reporting requirements of SARA 313.

All components of this product are on the TSCA list.

State Regulations: This product meets requirements of Southern California AQMD Rule 443.1 and Similar Regulations California Proposition 65: This product contains the following chemical known to the State of California to cause cancer: None.

SECTION 16: OTHER INFORMATION

All information, recommendations, and suggestions made by IDQ, Inc. ("Company") appearing herein concerning our product are based upon tests and data believed to be reliable. However, because of the variable characteristics of analytical procedures and samples, and the inability to control its customers' uses of the information and recommendations, or the related products or materials, Company makes NO WARRANTY, EXPRESS OR IMPLIED as to the accuracy of the information or recommendations or that such are fit for any general or specific purpose, whatsoever. Company shall have NO LIABILITY arising from the use by its customers or any third parties of the information and recommendations, and it shall be each customer's sole responsibility to determine the suitability for its own use of any information or recommendations provided by Company.